

WAMIT®

USER MANUAL

Versions 6.5, 6.5S

This User Manual has been prepared for users of WAMIT Version 6.5 and the second-order extension V6.5S.

WAMIT is distributed by WAMIT, Inc. under a special agreement with the Massachusetts Institute of Technology. Further information is available from the website shown below.

The WAMIT software and this User Manual are Copyrighted by WAMIT, Inc., and by the Massachusetts Institute of Technology. The User Manual can be downloaded from the website without a license, and individuals are permitted to make one hardcopy of the entire manual, or portions thereof, for use in conjunction with the WAMIT demonstration program. A hardcopy of the User Manual is provided to licensed users.

WAMIT, Inc.

117 Kendrick St. – Suite 300

Needham, MA 02494

USA

phone 617-739-4488

www.wamit.com

Copyright© 1998-2026 WAMIT, Incorporated and Massachusetts Institute of Technology.
No part of the WAMIT software or documentation may be reproduced, translated, or transmitted in any form without the express written permission of WAMIT, Inc.

WAMIT is a registered trademark of WAMIT, Inc.

Intel is a registered trademark of Intel Corporation.

Windows is a registered trademark of Microsoft Corporation.

MultiSurf and RGKernel are registered trademarks of AeroHydro, Inc.

Tecplot is a registered trademark of Amtec Engineering, Inc.

Linux is a registered trademark of Linux Torvalds.

TABLE OF CONTENTS

1. INTRODUCTION

- 1.1 WAMIT Version 6
- 1.2 Changes in WAMIT Version 6.0
- 1.3 Additional changes in Version 6.1
- 1.4 Additional changes in Version 6.2
- 1.5 Additional changes in Version 6.3
- 1.6 Additional changes in Version 6.4
- 1.7 Additional changes in Version 6.5

2. GETTING STARTED

- 2.1 Installation and setup
- 2.2 Demonstration programs
- 2.3 Standard test runs
- 2.4 Running Test 01
- 2.5 Running Test 11
- 2.6 Other test runs
- 2.7 Memory and storage restrictions
- 2.8 Modifying the input files

3. USING WAMIT

- 3.1 The Potential Control File (Alternative form 1)
- 3.2 The Potential Control File (Alternative form 2)
- 3.3 The Force Control File (Alternative form 1)
- 3.4 The Force Control File (Alternative form 2)
- 3.5 Definition of fixed or free modes
- 3.6 Filenames list F NAMES.WAM
- 3.7 Configuration file CONFIG.WAM or *.CFG
- 3.8 File names
- 3.9 File format
- 3.10 Uniform arrays of field points
- 3.11 Using the optional file BREAK.WAM
- 3.12 Assigning RAO'S in an external file

4. DEFINITION OF QUANTITIES EVALUATED BY WAMIT

- 4.1 Hydrostatic data
- 4.2 Added-mass and damping coefficients
- 4.3 Exciting forces
- 4.4 Body motions in waves
- 4.5 Hydrodynamic pressure
- 4.6 Free-surface elevation
- 4.7 Velocity vector on the body and in the fluid domain
- 4.8 Mean drift force and moment
- 4.9 Format of numeric output files
- 4.10 Body pressure output for the higher-order method
- 4.11 Body pressure and fluid velocity at specified points
- 4.12 Radiation and diffraction components of the pressure and velocity
- 4.13 Radiation pressure and velocity for zero and infinite periods

5. THE LOW-ORDER METHOD (ILOWHI=0)
 - 5.1 The Geometric Data File (GDF)
 - 5.2 Use of the source formulation (ISOR=1)
 - 5.3 Body near vertical walls
 - 5.4 Bodies with thin submerged elements
6. THE HIGHER-ORDER METHOD (ILOWHI=1)
 - 6.1 Subdivision of the body surface in patches and panels
 - 6.2 B-Spline representation of the solution
 - 6.3 Order of Gauss Quadratures
 - 6.4 The Geometric Data File
 - 6.5 Geometry represented by low-order panels (IGDEF=0)
 - 6.6 Geometry represented by B-Splines (IGDEF=1)
 - 6.7 Geometry represented by MultiSurf (IGDEF=2)
 - 6.8 Analytic representation of the geometry
 - 6.9 Modifying the DLL Subroutine GEOMXACT
 - 6.10 Bodies with thin submerged elements
 - 6.11 The Optional Spline Control File
 - 6.12 The use of default values to simplify inputs
 - 6.13 Advantages and disadvantages of the higher-order method
7. ANALYSIS OF MULTIPLE BODIES (NBODY > 1)
 - 7.1 Input to POTEN (IALTPOT= ± 1)
 - 7.2 Input to POTEN (IALTPOT=2)
 - 7.3 Input to FORCE (IALTFRC=1)
 - 7.4 Input to FORCE (IALTFRC=2)
 - 7.5 Input to FORCE (IALTFRC=3)
 - 7.6 Parameters in the CONFIG.WAM file
 - 7.7 Output
8. GENERALIZED BODY MODES (NEWMDS > 0)
 - 8.1 Input Files
 - 8.2 Using DEFMOD with the Low-Order Method
 - 8.3 Using the DLL Subroutine NEWMODES
 - 8.4 Hydrostatics
 - 8.5 NBODY Analysis
9. USE OF IRREGULAR FREQUENCY OPTION (IRR > 0)
 - 9.1 Input parameters
 - 9.2 Automatic free-surface discretization (IRR=2 and ILOWHI=0)
 - 9.3 Automatic free-surface discretization (IRR=3 and ILOWHI=0)
 - 9.4 Automatic free-surface discretization (IRR=3 and ILOWHI=1)
 - 9.5 Assigning different values of IRR for NBODY>1

10. SPECIAL TOPICS

- 10.1 Error messages and log files
- 10.2 Reserved file names
- 10.3 Scratch files
- 10.4 Memory requirements and number of unknowns
- 10.5 Modifying DLL files
- 10.6 Auxiliary output files for the geometry
- 10.7 Internal tanks
- 10.8 Trimmed waterlines
- 10.9 Radiated waves from wavemakers in tank walls
- 10.10 Bodies and wavemakers with vertical walls

11. VERSION 6.5S (Second-order module)

- 11.1 The Configuration file (CFG)
- 11.2 The Force control file (FRC)
- 11.3 The Potential control file 2 (PT2)
- 11.4 The Free surface data file (FDF)
- 11.5 FDF for the low-order method (ILOWHO=0)
- 11.6 FDF for the higher-order method (ILOWHI=1)
- 11.7 Optional spline control file (ILOWHI=1)
- 11.8 Special topics on FDF
- 11.9 Fnames.wam
- 11.10 Definitions of output
- 11.11 Numeric output files
- 11.12 Installation and setup

12. THEORY

- 12.1 The boundary-value problem
- 12.2 Integral equations for the velocity potential
- 12.3 Integral equations for the source formulation
- 12.4 Discretization of the integral equations in the low-order method (ILOWHI=0)
- 12.5 Discretization of the integral equations in the higher-order method (ILOWHI=1)
- 12.6 Solution of the linear systems
- 12.7 Mean drift force and moment based on pressure integration
- 12.8 Removal of irregular frequencies
- 12.9 Integral equation for bodies with zero thickness
- 12.10 Mean drift force and moment using control surface
- 12.11 Internal tank effects

13. THE F2T UTILITY

- 13.1 Definitions of radiation and diffraction outputs
- 13.2 Acquiring input data for F2T with WAMIT
- 13.3 How to use F2T
- 13.4 Output files
- 13.5 Options 5,6,7
- 13.6 Theory
- 13.7 Dimensional input and output data

14. MEAN DRIFT FORCES USING CONTROL SURFACE

- 14.1 Control surface file (CSF)
- 14.2 Low-order control surface file
- 14.3 Higher-order control surface file
- 14.4 Automatic control surfaces
- 14.5 Output

REFERENCES

APPENDIX A – DESCRIPTION OF TEST RUNS

- A.1 Truncated vertical cylinder (TEST01)
- A.2 Irregular-frequency removal (TEST02)
- A.3 Local pressure drift force (TEST03)
- A.4 Body near a wall (TEST04)
- A.5 Multiple bodies (TEST05)
- A.6 The ISSC Tension-Leg Platform (TEST06)
- A.7 The ISSC Tension-Leg Platform (TEST07)
- A.8 Elastic column with generalized modes (TEST08)
- A.9 Spar with three strakes (TEST09)
- A.11 Higher-order analysis of circular cylinder (TEST11)
- A.12 Irregular-frequency removal (TEST12)
- A.13 Multiple bodies (TEST13)
- A.14 ISSC TLP (TEST14)
- A.15 Semi-Sub (TEST15)
- A.16 Barge with bending modes (TEST16)
- A.17 Cylinder with moonpool (TEST17)
- A.18 Elastic column (TEST18)
- A.19 Catamaran barge (TEST19)
- A.20 MultiSurf Barge (TEST20)
- A.21 Spar with three strakes (TEST21)
- A.22 FPSO with two internal tanks (TEST22)
- A.23 Radiated wave field from a bank of wavemakers (TEST23)
- A.24 Motions of a hinged vessel (TEST24)

APPENDIX B – DESCRIPTION OF SECOND-ORDER TEST RUNS

- B.1 Sphere (TEST101)
- B.2 Bottom mounted cylinder (TEST102)
- B.3 Multiple bodies (TEST103)
- B.4 Ellipsoid with a tank (TEST 104)
- B.11 Sphere (TEST111)
- B.12 Bottom mounted cylinder (TEST112)
- B.13 Multiple bodies (TEST113)
- B.14 Ellipsoid with a tank (TEST 114)

APPENDIX C – USING THE WAMIT-RGKERNEL INTERFACE (By J. S. Letcher, Jr.)